



DESCRIPTION

Six Layer 1000 Litre Top fill / Bottom Discharge Liquid Liner. 2" & 3" BSP fill x SAS DN50 discharge (White Push fit), Tinted LLDPE

Application:

This liner is specified for use with the AQA Tank Solutions, for applications where fill or exposure temperatures do not exceed 80°Centigrade. This liner meets European and FDA requirements for food contact materials.

Parts list

Fill	2" & 3" Fill Gland	B20.418
	2" & 3" BSP Blue Gland	
	2" & 3" BSP Yellow Screw Cap	
Discharge	SAS Blue Gland	B20.127
	SAS Valve WHITE	B20.126
Fill Side Layers		
1 Outer film layer	Flexcene Tinted 60µm	B10.054
2 Inner film layer	Flexcene Tinted 60µm	B10.054
3 Contact film layer	Flexcene Tinted 60µm	B10.054
Discharge Side Layers		
1 Outer film layer	Flexcene Tinted 80µm	B10.055
2 Inner film layer	Flexcene Tinted 80µm	B10.055
3 Contact film layer	Flexcene Tinted 80µm	B10.055

Packaging spec

Qty per carton:

6 Qty

Carton weight:

13.38Kg

Per pallet:

150 liners

Liner weight:

1.98Kg